MADE IN ITALY

Home safes

CERTIFIED UNI EN 14450, GRADE S2

ICIM



Discover the range

MOTTURA

safeguarding your security

Certified safes



Personal Electronic
Lock with electronic combination system



Personal
Key and mechanical combination locking



Personal
With four-dial mechanical combination locking system



Personal
Key locking



No Problem Elettronica
Lock with electronic combination system



No Problem
Key and mechanical combination locking



Under
Key locking
Key and mechanical combination locking

Special safes



Special
Key locking

PERSONAL ELECTRONIC

> WITH ELECTRONIC COMBINATION LOCKING SYSTEM



- All new Mottura safes feature a keypad with a new design.
- Motorised movement of contoured bolts.
- Manganese protection extended to protect front bolts (illustrated in detail).
- Settable with combinations from 6 to 8 numbers.
- An internal LED light switches on automatically when the safe is open.
- Dual codes possible on request.
- Powered by 6 x 1.5 V AA batteries.
- Emergency ext. power supply by 9V battery.
- Shelf supplied as standard.
- **Lock with UNI EN 1300, Grade A certification.**
- Built-in horizontal (art. 11.3115 - 11.3330) or vertical (11.3445) electronic combination safe.
- Door thickness: mm 10; frame thickness: mm 12.

DEPTHS AVAILABLE:
mm. 200 - 250







REMOVABLE DOOR.

PERSONAL

> KEY AND MECHANICAL COMBINATION LOCKING



- Built-in model with key and mechanical combination locking system.
- Manganese protection extended to protect
- contoured front bolts.
- Spare lever with anti-tampering protection.
- Shelf/shelves supplied as standard.
- **Lock with UNI EN 1300, Grade A certification.**
- Available as horizontal (art. 11.2115 - 11.2330) and vertical (art. 11.2420 - 11.2530) variants.
- Door thickness: from 10 mm to 12 mm; frame thickness: from 12 mm to 15 mm.

REMOVABLE DOOR.



DEPTHS AVAILABLE:
mm. 150 - 200 - 250 - 300

ONLY ON VERSION 112115/20/25

NO PROBLEM

> WITH ELECTRONIC COMBINATION LOCKING SYSTEM

> KEY AND MECHANICAL COMBINATION LOCKING



- With anchor points (supplied) for securing to both the wall and the floor.
- The safe is encased entirely in three layers of steel, for a total thickness of 9 mm.
- Shelf/shelves supplied as standard.
- **Lock with UNI EN 1300, Grade A certification.**
- Door thickness: from 10 mm to 12 mm; frame thickness: from 12 mm to 15 mm.

Other features as Personal series.

REMOVABLE DOOR.



VERSION WITH ELECTRONIC COMBINATION LOCK



VERSION WITH KEY AND MECHANICAL COMBINATION



DEPTHS AVAILABLE:
mm. 230 - 285 - 325

PERSONAL

> WITH 4-DIAL MECHANICAL COMBINATION LOCKING SYSTEM



- Built-in safe with new 4-dial mechanical combination locking system which significantly increases the number of possible combinations (160,000).
- Manganese protection extended to protect contoured front bolts.
- Shelf/shelves supplied as standard.
- **Lock with UNI EN 1300, Grade A certification.**
- Available as horizontal (art. 11.5115 - 11.5325) and vertical (art. 11.5530) variants.
- Door thickness: from 10 mm to 12 mm; frame thickness: from 12 mm to 15 mm

REMOVABLE DOOR.







DEPTHS AVAILABLE:
mm. 150 - 200 - 250 - 300

ONLY ON VERSION 115115/20/25

UNDER

> WITH KEY LOCKING SYSTEM
> KEY AND MECHANICAL COMBINATION LOCKING



- Recessed floor model with key locking system and key + mechanical combination locking system.
- Manganese protection extended to protect contoured front bolts.
- Safe with top door for installation under floor level.
- The opening side of this model has an external protection that offers easy levelling with any type of floor.
- Spare lever with anti-tampering protection.
- Safety damper to prevent accidental closing of door.
- **Lock with UNI EN 1300, Grade A certification.**
- Door thickness: mm 10; frame thickness: mm 12.

REMOVABLE DOOR.

VERSION WITH KEY LOCKING SYSTEM



VERSION WITH KEY LOCK SYSTEM AND MECHANICAL COMBINATION







DEPTHS AVAILABLE:
mm. 325

ONLY ON VERSION 111131/2131

PERSONAL

> WITH KEY LOCKING SYSTEM



- Built-in model with key locking system.
- Manganese protection extended to protect contoured front bolts.
- Spare lever with anti-tampering protection.
- Shelf/shelves supplied as standard.
- **Lock with UNI EN 1300, Grade A certification.**
- Available as horizontal (art. 11.1120 - 11.1320).
- Door thickness: from 10 mm to 12 mm; frame thickness: from 12 mm to 15 mm.

REMOVABLE DOOR.







DEPTHS AVAILABLE:
mm. 200 - 250

ONLY ON VERSION
111120

SPECIAL

> WITH KEY LOCKING SYSTEM



Version with key
- Spare lever with anti-tampering protection.

Electronic version with membrane keypad
- With powered round bolts; next generation electronics.
- Settable with combinations from 6 to 8 numbers.
- Dual codes possible on request.
- Exterior finish in gloss midnight blue; single-piece weldless frame.
- Hinges designed for maximum door opening angle.
- Shelf supplied as standard.
- Powered by 6 x 1.5 V AA batteries.
- Emergency ext. power supply by 9V battery.
- Door thickness: 8 mm; frame thickness: 8 mm.

DEPTHS AVAILABLE:
mm. 150 - 200 - 250

Dimensions

10/2026

KEY	KEY AND MECHANICAL COMBINATION	ELECTRONIC COMBINATION	MECHANICAL COMBINATION	HEIGHT [mm]	WIDTH [mm]	DEPTH [mm]
PERSONAL						
–	11.2115	–	11.5115	230	350	150
11.1120	11.2120	11.3120	11.5120	230	350	200
11.1220	11.2220	11.3220	11.5220	290	410	200
11.1320	11.2320	11.3320	11.5320	360	460	200
–	11.2420	–	–	430	295	200
–	11.2440	–	–	490	370	200
–	11.2125	11.3125	11.5125	230	350	250
11.1225	11.2225	11.3225	11.5225	290	410	250
–	11.2325	11.3325	11.5325	360	460	250
–	11.2425	–	–	430	295	250
–	11.2445	11.3445	–	490	370	250
–	11.2525	–	–	680	480	250
–	11.2230	–	11.5230	290	410	300
–	11.2330	–	–	360	460	300
–	11.2530	–	11.5530	680	480	300
SPECIAL						
11.6311	–	–	–	170	265	150
11.6321	–	–	–	200	290	150
11.6331	–	–	–	240	330	150
11.6312	–	–	–	170	265	200
11.6322	–	–	–	200	290	200
11.6332	–	–	–	240	330	200
11.6342	–	11.6642	–	290	390	200
11.6323	–	–	–	200	290	250
11.6333	–	–	–	240	330	250
11.6343	–	11.6643	–	290	390	250
11.6372	–	–	–	330	240	200
NO PROBLEM						
–	11.KC130	11.KE130	–	235	355	230
–	11.KC233	11.KE233	–	295	415	285
–	11.KC444	11.KE444	–	495	375	325
UNDER						
11.1131	11.2131	–	–	265	385	325
11.1231	11.2231	–	–	325	445	325
–	11.2331	–	–	395	495	325
SPECIAL						
11.6311	–	–	–	170	265	150
11.6312	–	–	–	170	265	200
11.6322	–	–	–	200	290	200
11.6332	–	–	–	240	330	200
11.6342	–	–	–	290	390	200
11.6343	–	–	–	290	390	250
11.6372	–	–	–	330	240	200

COMPANY WITH
MANAGEMENT SYSTEM
CERTIFIED BY DNV
ISO 9001 • ISO 45001

Mottura Serrature di Sicurezza SpA

Strada Antica di Francia, 34
10057 Sant'Ambrogio di Torino (TO) - Italia