

10

CUPBOARD SAFES FOR HOTEL, RESORT, SHIPS



safeguarding your security

An exclusive collection

From the experience of a company that is able to offer different solutions for different security requirements comes Hokey®, a complete range of free standing safes for hotel, resort and ships, but also suitable for domestic use. A leading-edge project that comes from an ex-clusive design, understood in the broadest sense: not just pleasing aesthetic touches and range of colours, but also rationalization in dimensions and overall volume with regard to the placing and use.

It is a collection that perfectly combines three fundamental demands:

- ease of installation
- the ability to blend the safe into its surroundings, thanks to the "soft-touch" colours on the doors
- great ease of use.

The paint finish with cataphoresis treatment (optional) which ensures a high resistance to corrosion and is advisable for use in particularly difficult environment such as, for example, constant exposure to sea air. Hokey® safes do not require any masonry work: the back and base are supplied with holes for rapid fixing to walls, cupboards, furnishings and closets.

Locking systems

Hokey® safes are available with four types of lock:

- Electronic with standard MASTER CODE (fig. 1, 2)
- Extractable europrofile cylinder (fig. 3)
- Double-bitted key (fig. 4)
- Double-bitted key and mechanical combination (fig. 5)

The electronic safes can be supplied in two different versions :

1. Emergency mechanical opening with europrofile cylinder near the keyboard (HE7900/8000/8020/8100 series)
2. Opening with external power supply (alkaline battery, type PP3, 9 volts), in case of power failure (HE8010,8030,8110 series) (fig. 2).

For hotel, resort or ship use, the models with extractable cylinder (fig. 3) or double-bitted key only (fig. 4) can be supplied with a master key that opens all safes of the same group (HM series).

Optional

- Left hand opening (fig. 6)
- Customized version

Colour range electronic safes (10.HE...)

The basic color is Anthracite grey. On request is available in ivory (specify in the order).



Anthracite grey

Ivory

10.HE7900

Locking with electronic combination and emergency mechanical opening with europrofile cylinder (half cylinder type M - length 31 mm)



- PIN code (6 digit min - 8 digit max) allows millions of combinations.
- Standard MASTER CODE supplied.
- Keyboard with a new design with multilingual alphanumeric display.
- The door opens automatically once unlocked, thanks to the incorporated spring.
- With every new setting, the system cancels the previous code
- Powered by 6 alkaline batteries "AA" type 1,5 volts.
- Emergency mechanical opening with europrofile cylinder (included) near the keyboard.
- Low energy consumption and no maintenance required.
- Multinational network socket for possible charger (110 to 230 VAC).

Electronic

Art.	External frame dimensions in mm			Internal frame dimensions in mm			Door passage dim. in mm		Thickness mm		Weight Kg.	Bolts n°
	height	width	depth	height	width	depth	height	width	Door	Shell		
10.HE7900	190	430	350	186	426	285	150	325	3	2	14,5	1

10.HE8000

Locking with electronic combination and **emergency mechanical opening with europrofile cylinder** (half cylinder type M - length 31 mm)




- Six-digit PIN allows millions of combinations.
- Standard MASTER CODE supplied.
- Keys with braille embossing are extremely sensitive and precise.
- The door opens automatically once unlocked, thanks to the incorporated spring.
- With every new setting, the system cancels the previous code.
- Powered by 6 alkaline batteries "AA" type 1,5 volts.
- Emergency mechanical opening with europrofile cylinder (included) near the keyboard.
- Low energy consumption and no maintenance required.
- Colours for the door: anthracite grey, and ivory, all with "soft-touch" finishing.
- Shell and frame grey ral 7031.
- Indelible pad print on the door with instructions of use in four languages (Italian, English, French, Spanish).

Electronic

Art.	External frame dimensions in mm			Internal frame dimensions in mm			Door passage dim. in mm		Thickness mm		Weight Kg.	Bolts n°
	height	width	depth	height	width	depth	height	width	Door	Shell		
10.HE8000	250	370	280	246	366	233	200	300	6	2	15,5	1
10.HE8020	250	370	400	246	366	353	200	300	6	2	18,1	1
10.HE8100	550	365	450	546	361	400	487	300	6	3	50	2

10.HE8110

Locking with electronic combination and **opening with external battery in case of power failure**



This series is composed of three models with the some sizes and characteristics of HE8000/8020/ 8100, but equipped with a different emergency opening: in case of power failure possibility of opening with external power supply (alkaline type PP3 9 volts).
The vertical model (Art. 10.HE8110) allows the storage of a business suitcase.

Electronic

Art.	External frame dimensions in mm			Internal frame dimensions in mm			Door passage dim. in mm		Thickness mm		Weight Kg.	Bolts n°
	height	width	depth	height	width	depth	height	width	Door	Shell		
10.HE8010	250	370	280	246	366	233	200	300	6	2	15,4	1
10.HE8030	250	370	400	246	366	353	200	300	6	2	18	1
10.HE8110	550	365	450	546	361	400	487	300	6	3	50	2

10.HS6500



Locking with europrofile cylinder

- for 10.HM6000, HS6000, HS 6010
(half cylinder type M - length 31 mm)
- for 10.HM6500, HS6500, HS 6510
(half cylinder type M - length 36 mm)



This model especially offers a double advantage: the comfort of the short key and the possibility of fixing the cylinder in the safe directly by the end user. The europrofile cylinder can be easily removed in case of need, pulling the pivot inside the door.
HM... versions are supplied with a master key that opens all safes of the same group.

Lock with europrofile cylinder C28 (included)

Art.	External frame dimensions in mm			Internal frame dimensions in mm			Door passage dim. in mm		Thickness mm		Weight Kg.	Bolts n°
	height	width	depth	height	width	depth	height	width	Door	Shell		
10.HS6000	175	270	225	170	265	177	109	170	3	2	6,6	2
10.HS6500	250	370	280	246	366	233	200	300	6	2	14,5	2

Lock with europrofile cylinder (not included)

Art.	External frame dimensions in mm			Internal frame dimensions in mm			Door passage dim. in mm		Thickness mm		Weight Kg.	Bolts n°
	height	width	depth	height	width	depth	height	width	Door	Shell		
10.HS6010	175	270	225	170	265	177	109	170	3	2	6,5	2
10.HS6510	250	370	280	246	366	233	200	300	6	2	14,5	2

Lock with cylinder C28 (included) with master key

Art.	External frame dimensions in mm			Internal frame dimensions in mm			Door passage dim. in mm		Thickness mm		Weight Kg.	Bolts n°
	height	width	depth	height	width	depth	height	width	Door	Shell		
10.HM6000	175	270	225	170	265	177	109	170	3	2	6,6	2
10.HM6500	250	370	280	246	366	233	200	300	6	2	14,5	2

10.HS5800

10.HS5000



Lock with double-bitted key



The double-bitted key ensures simplicity and superlative reliability.

Lock with double-bitted key

Art.	External frame dimensions in mm			Internal frame dimensions in mm			Door passage dim. in mm		Thickness mm		Weight Kg.	Bolts n°
	height	width	depth	height	width	depth	height	width	Door	Shell		
10.HS5000	175	270	225	170	265	177	109	170	3	2	6,5	2
10.HS5500	250	370	280	246	366	233	200	300	6	2	14,7	2
10.HS5600	297	415	292	293	411	232	210	315	6	2	19,1	2+2
10.HS5800	495	375	323	491	371	263	390	250	6	2	26	3+2

10.HC5800

10.HC5600



Key and mechanical combination locking



The double-bitted lock ensures total reliability, and is complemented by a mechanical combination system for additional security.

Two different formats specifically created for storing documents, PDAs, cameras etc..

Key and mechanical combination

Art.	External frame dimensions in mm			Internal frame dimensions in mm			Door passage dim. in mm		Thickness mm		Weight Kg.	Bolts n°	
	height	width	depth	height	width	depth	height	width	Door	Shell			
10.HC5600	297	415	292	293	411	232	210	315	6	2	20,1	2+2	
10.HC5800	495	375	323	491	371	263	390	250	6	2	27	3+2	